

Tubo fino rectangular o cuadrado para aplicaciones mecánicas calibrado exteriormente
Medidas, masas referidas a la longitud

Longitud de los lados			Masas referidas a la longitud, en kg/m para espesores t								
Medida nominal h	Medida nominal b	Desviación de medidas límite h y b	1	1.25	1.5	2	2.5	3	4	5	
15	15	± 0.20	0.438	0.537	0.632*	0.810					
18	18	± 0.20	0.532	0.655	0.773	0.998					
20	10	± 0.20	0.438	0.537	0.632*	0.810					
	15		0.516	0.635	0.750*	0.967					
20	20	± 0.20	0.595	0.733	0.868*	1.12*	----				
	25		0.595	0.733	0.868	1.12	----				
25	15	± 0.25	0.752	0.930	1.10	1.44	----				
	20		0.595	0.733	0.868*	1.12	----				
30	10	± 0.25	0.673	0.831	0.985*	1.28	----				
	15		0.752	0.930	1.10*	1.44	----				
	20		0.909	1.13	1.34*	1.75*	2.15	2.39	----		
34	20	± 0.25	0.815	1.01	1.20	1.56	----				
	34		1.03	1.28	1.53	2.00	2.46	2.77	----		
35	20	± 0.25	0.830	1.03	1.22*	1.59	1.95	----			
	25		0.909	1.13	1.34	1.75	2.15	2.39	----		
36	35	± 0.25	1.07	1.32	1.57*	2.07*	2.54	2.86	----		
	11		0.705	0.871	1.03	1.34	----				
40	20	± 0.30			1.34*	1.75*	2.15	2.39	----		
	25				1.46	1.91	2.34	2.63	----		
	30					1.57*	2.07*	2.54	2.86	----	
	40					1.81*	2.38*	2.93	3.33	4.25	
45	45	± 0.30			2.05	2.69	3.33	3.80	4.88		
50	20	± 0.30			1.57*	2.07*	2.54	2.86	----		
	25				1.69	2.22	2.74	3.10	----		
	30					1.81*	2.38*	2.93	3.33	4.25	
	34					1.90	2.51	3.09	3.52	4.50	
	40					2.05*	2.69*	3.33	3.80	4.88	
55	50	± 0.40			2.28*	3.01*	3.72	4.28	5.51	----	
	34				2.02	2.66	3.29	3.76	4.82	----	
60	20	± 0.40				2.38	2.93	3.33	----	----	
	30					2.69*	3.33	3.80	4.88	----	
	40					3.01*	3.72	4.28	5.51	----	
	50					3.32	4.11	4.75	6.14	----	
70	60	± 0.50				3.64*	4.50	5.22	6.76	8.13	
	40					3.32*	4.11	4.75	6.14	----	
80	70	± 0.60				4.26*	5.29	6.16	8.02	9.70	
	20					3.01	3.72	4.28	----	----	
	30					3.32*	4.11	4.75	----	----	
	40					3.64*	4.50	5.22	6.76	8.13	
	50					3.95	4.90	5.69	7.39	8.91	
	60					4.26	5.29	6.16	8.02	9.70	
90	80	± 0.75				4.89*	6.07	7.10	9.28	11.3	
	90					5.52	6.86	8.04	10.5	12.8	
	40					4.26*	5.29	6.16	8.02	9.70	
	50					4.58*	5.68	6.63	8.65	10.5	
100	60	± 0.80				4.89	6.07	7.10	9.28	11.3	
	80					5.52	6.86	8.04	10.5	12.8	
	100					6.15*	7.64	8.99	11.8	14.4	
120	40	± 0.80				4.89	6.07	7.10	9.29	11.3	
	60					5.52*	6.86	8.04	10.5	12.8	

* Medidas más comerciales.